


specification DS45

LOA	13.72 m	45' 00"
LWL	12.93 m	42' 42''
Beam	4.57 m	14' 12''
Draft	2.04 m	6' 8''
	1.60 m	5' 3''
Displacement approx.	14.00 t	30,864 lbs
Ballast approx.	4.30 t	9,479 lbs
Engine approx.	Diesel 78 kW	107 hp
Fresh water	690 l	182 gal
Fuel tank	640 I	169 gal
CE Certifcate	A - 12	
Mast lenght above WL	21.80 m	71' 6"
Main approx.	64.60 m ²	695 sq ft
Jib approx.	41.90 m ²	451 sq ft
Total sail area approx.	106.50 m ²	1,146 sq ft
Rlg	I 18.60 m	61' 00"
	J 5.10 m	16' 9''
	P 18.24 m	59' 10''
	E 6.00 m	19' 8''
Design	Dixon Yacht Design	Watervision
Interior	Design Unlimited	



deck- & interiorlayouts DS45



standard specification DS45

HULL

- · 6 hull windows (3 each side)
- GRP hull, isophthalic gelocat: Off White (RAL 9003), 1st layer vinyl ester resin with balsa sandwich core.
- · Waterline and cove line, gelcoat colour: Moody Grey (RAL 7034 - only with XA1000)

KEEL

- · L-keel, cast iron, draft: 1.99 m
- GRP rudder with sea-water resistant aluminium shaft and selfaligning bearings

LAYOUT & INTERIOR

- · A1: Master cabin with island double berth, storage space, vanity area and head with separate shower stall add. guest head
- · B1: 2 aft cabins with double berth and storage
- C1: Saloon with full functional L-galley and dining area on stb chart table on port
- · D1: 2 cockpit locker with dinghy storage
- · 3-burner gas stove with oven, waste bin, 12 V fridge approx. 140 I, sink with mixing tab
- · Interior furniture in high quality marine plywood, satin varnished
- \cdot Sliding door in deckhouse
- · Worktop in galley Corian, colour: Grained Black

WOOD (FURNITURE, FLOORBOARD)

- · Furniture Traditional Mahogany satin varnish
- · Floorboard New Zealand Acacia

UPHOLSTERY, CARPETS & CURTAINS

- · Comfort mattrasses for all berths
- · Upholstery kent, colour: Cream
- · Upholstery sleeping cabin trims yorkshire leather, colour: Ivory

DECK & OUTSIDE EQUIPMENT

- GRP deck with antislip surface, gelcoat colour: Off White (RAL 9003), 1st layer vinyl ester resin with blasa sandwich core. Cockpit locker on port and stb, stern locker, stowage for running rigging at helm position, anchor locker at bow.
- · Teak on cockpit bottom, -benches and side deck
- \cdot Twin wheel steering system with emergency tiller
- \cdot 2 stainless steel steering wheels with leather cover
- · Cockpit table, GRP with foldable tops
- · Pulpit and pushpit, stainless steel
- · Railing, stainless steel tube incl. stanchions
- Halyards and control lines in cockpit at helm position, stern locker, 2 cockpit lockers, stowage for running rigging at helm position, 6 retractable mooring cleats, handrail on coach roof, anchor arm and anchor locker

- · 2 LEWMAR 55 EST EVO electrical secondary winches (only with XH1001)
- Bathing platform, manual fold-out with swimming ladder
- · Delta-anchor 25 kg, galvanized with 60 m galvanized chain, dia. 10 mm
- · Self tacking jib system
- · Mainsheet system
- Panoramic deck saloon windows with center hatch, openable, 4 coach roof windows - openable, glass on forward coach roof with big hatch, openable, 4 deck saloon hatches, 2 coach roof hatches

RIG & SAILS

- · Rig, anodized aluminium, deck stepped, with kicker, standing and running rigging and 2 reefs
- · ELVSTRÖM Dacron sails full battened, main and iih

NAVIGATION & INSTRUMENTS

- · Illuminated compass at each helm
- · Navigation lights LED
- Raymarine i70s multifunction display in cockpit, incl. transducer (speed/depth/temperature)

PROPULSION

- · Fuel tank, approx. 640 I
- · Engine (Diesel, approx. 107 hp) shaft drive, 3-blade folding propeller
- · Electronic throttle control at helm position on stb
- · Bowthruster, 24 V, retractable, incl. battery

EQUIPMENT

- · 12 V and 230 V electric system with main panels and 230 V shore power and sockets in cabins and heads
- · AGM battery set, capacity: 1x 90 Ah + 3x 160 Ah AGM
- · Country Version: EU / AUS
- · Battery charger 50 A
- · Manual toilet with sea water flush (guest cabin)
- · Manual toilet with sea water flush (master cabin)
- · Shower unit in cockpit, warm-/coldwater
- · LPG gas system, 2 bottles in stowage
- · Blackwater system (appr. 50 I per head) with deck extraction and seacock for head
- Freshwater system with electric pump and 40 I hotwater, heated by main engine
- · Fresh water tank, appr. 690 I

standard specification DS45

SHIPPING & TRANSPORT

- · CE Certificate cat. A 12
- · Owners manual
- · EC Type Examination Certificate